SAFETY DATA SHEET

SECTION 1: Identification

Trade Name: 806 SPRAYABLE PART B

Emergency phone

Supplier and manufacturer:

PERS 800-633-8253

MADEWELL PRODUCTS CORPORATION 7561 INDUSTRIAL COURT ALPHARETTA GA 30004

PHONE: 770-475-8199 FAX: 770-475-8167

SECTION 2: Hazard(s) Identification

GHS Ratings:

Carcinogen

1A

Known Human Carcinogen Based on human evidence

GHS Hazards

H350

May cause cancer

GHS Precautions

P201

Obtain special instructions before use

P202

Do not handle until all safety precautions have been read and understood

P281

Use personal protective equipment as required

P308+P313

IF exposed or concerned: Get medical advice/attention

P405

Store locked up

P501

Dispose of contents/container to ...

Signal Word: Danger



SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

	-	
Chemical Name	CAS number	Weight Concentration %
PHENALKAMINE	1613633-26-3	80.00% - 90.00%
TALC	14807-96-6	1.00% - 5.00%
CARBON BLACK	1333-86-4	1.00% - 5.00%

SECTION 4: First Aid Measures

Inhalation: Move person to fresh air. If breathing is irregular, provide artificial respiration; if there are breathing difficulties, administer oxygen; get medical attention.

Eye contact: Bathe the eye with running water for at least 15 minutes, lifting upper and lower eyelids. Get medical attention if

SDS for: 806 B SPRAYABLE

Page 1 of 6

symptons persist.

Skin contact: Drench the affected area immediately with plenty of water, remove contaminated clothing. Wash thoroughly with soap and water for at least 15 minutes. Seek medical attention if irritation, rash, or other adverse effects occur.

Ingestion: DO NOT induce vomiting: rinse mouth then drink plenty of water. Call nearest poison center or physician immediately.

Most important symptoms and effects, both acute and delayed

Skin irritation, allergic reactions.

SECTION 5: Fire Fighting Measures

Flash Point: 104 C (219 F)

LEL: N/A

UEL: N/A

Exginguishing media: Carbon dioxide, alcohol resistant foam, dry chemical, water fog; use water spray to cool fire-exposed containers. Do not use direct water stream which may spread fire.

Unusual fire/ expl. hazards: Exposure to decomposition products may be harmfult to health; combustion products may include but are not limited to: carbon monoxide, carbon dioxide, phenolics; smoke may contain particles of the original material as well. Prevent firefighting waters from entering sewer or waterways.

Fire equipment: Use protective fire fighting clothing and positive pressure self-contained breathing apparatus to protect against potential harmful and/or irritating fumes. Do not use high volume water jet as this may spread the area of the fire.

SECTION 6: Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Isolate area; ensure adequate ventilation; use appropriate personal protection equipment; avoid breathing mist, vapors, spray; avoid contact with skin, eyes and closthing, keep unnecessary and unprotected personnel from entering the involved area.

Environment precautions:

Prevent contamination of soil and water. Prevent from spreading or entering into drains ditches, waterways by using sand, earth or

Method and material for containment and cleaning up

Absorb with sand, diatomaceous earth or universal binders and collect into suitable disposal container. Dispose of in accordance with applicable local and federal environmental control laws and regulations.

SECTION 7: Handling and Storage

Precautions for safe handling

Ensure adequate ventilation of workplace and storage areas; avoid skin contact; do not breathe mist, vapors, spray; use recommended personal protective equipment; wash thoroughly after handling. Do not eat, drink or smoke in the work area. Avoid use of electric band heaters (failures of such heaters have been reported to cause drums of liquid epoxy resin to explode and catch fire). Never apply a direct flame to any container of product.

Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well-ventilated place. Keep away from incompatible materials, Keep container tightly closed. Recommended storage temperature: 10-35C (50-95F)

SECTION 8: Exposure Controls/Personal Protection				
Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits	
PHENALKAMINE 1613633-26-3	Not Established	Not Established	Not Established	
TALC 14807-96-6	2MG/M3 RESPIRABLE FRACTION	2MG/M3	Not Established	
CARBON BLACK 1333-86-4	TWA 3.5 MG/M3	TLV 3.5 MG/M3	Not Established	

Occupational exposure limits: OSHA/PEL: None established.

Ensure adequate ventilation through local exhaust.

Follow good industrial workplace practices; do not eat, drink or smoke wihile handling; wash hands before breaks and at end of

SDS for: 806 B SPRAYABLE Page 2 of 6

Eye/face protection

Use safety glasses with side shields.

Skin protection

Wear impervious clothing as necessary to protect against product contact,. Necessity for boots, apron, face shield, etc. will be dependent on any hazards presented in the work process.

Respiratory protection

Although no exposure limits have been established, respiratory protection may be of use if any respiratory irritation or discomfort is noted; if the material is processed at elevated temperatures without adequate ventilation it may be necessary to wear an air-purifying respirator with organic vapor cartridge; respirator use should follow the guidelines of an established respiratory protection program in compliance with 29CVF1910.134.

Hand protection

Wear nitrile rubber, nitrile, neoprene, PVC or other suitable impervious gloves. Gloves selected musthave a breakthrough rating appropriate for the work shift.

Other protective equipment

Teh type and degree of personal protective equipment appropriate willk depend on the specific work operation Eye wash stations and emergency showers should be available.

SECTION 9: Physical and Chemical Properties

Physical state: liquid Initial Boiling Point: >117C Melting Point: Not applicable Type of Odor: Slight amine Odor Threshold: Not determined

Flammability Classification: Combustible IIIB

Flash Point: 104C

Vapor Pressure: <8 hPa @ 25C

Vapor Density: >1 Bulk density: 8.33 lbs/gal Evaporation Rate: <1

Decomposition Temperature: >160C

Solubility in Water: Nil

pH: Alkaline

Autoignition Temperature: No data available

Specific Gravity: 1 Viscosity: 500-1500

SECTION 10: STABILITY AND REACTIVITY

Reactivity

No dangerous reaction is known uder normal use and storage conditions.

Stability: Stable under normal use and storage conditions.

Possibility of hazardous reactions: Mixtures with strongly acidic or strongly alkaline materials may produce and exothermic reaction.

Conditions to avoid: Elevated temperatures and sources of ignition.

Materials to avoid: Strong oxidizing agents, strong acids, strong reducing agents. Hazardous decomposition products: By fire: carbon monoxide, aldehydes

SECTION 11: Toxicological Information

Mixture Toxicity Component Toxicity

1333-86-4

CARBON BLACK

Dermal LD50: 3 g/kg (RABBIT)

SDS for: 806 B SPRAYABLE

Page 3 of 6

Acute Oral Toxicity: LD50(rat): >2000 mg/kg Acute Dermal Toxicity: LD50(rabbit), > 20,00 mg/kg

Skin Corrosion/irritation (rabbit): Causes slight skin irritation

Serious Eye Damage eye Irritation (rabbit): Causes serious eye irritation; corneal injury is not likely.

Skin: Causes mild skin irritation; may cause sensitization; once sensitized, a severe allergic reaction may ocur when subsequently exposed to very low levels.

Eyes: Causes serious eye irritation; pain, irritation, watering, redness.

Ingestion: Low toxicity; incidental ingestion of small amounts not anticipated to be harmful.

Inhalation: Low volatility; not expected to be a significant route of exposure.

Specific Target Organ Toxicity - single exposure (STOT-se): Not classified based on available data. Specific Target Organ Toxicity - repeated exposure (STOT-re): Not classified based on available data.

Effects of Overexposure

Carcinogenicity: Not Classified based on available date., Not listed by IARC, NTP, OSHA

CAS Number

Description

% Weight

Carcinogen Rating

14807-96-6

TALC

1% - 5%

TALC:

Chronic Health Effects: No data available.

SECTION 12 - ECOLOGICAL INFORMATION

Acute/prolonged toxicity to fish

No data available

Acute/prolonged toxicity to aquatic invertebrates

No data available

Acute/prolonged toxicity to aquatic plants

No data available

Toxicity ot bacyteria, to soil dwelling organisms and to terrestrial plants

No Data available

Chronic toxicity to aquatic organisms

No data available

General effect

No specific data for this product: toxicity to aquatic organisms anticipated to be negligible.

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data availabel

Results of PBT and vPvB assessment (EC reg. 453/2010)

Not classified as persistent, bioaccumulative and toxic Not classified as very persistent or very bioaccumulative

Component Ecotoxicity

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal: Do not dump to ground, sewers or wtercourses. Reuse uncontaminated material wehn possilbe. All methods of disposal must be in compliance with all applicable federal, state and local environmental control laws and regulations. Weste characterization

SDS for: 806 B SPRAYABLE

according to RCRA guidelines and compliance wiyth applicable laws are the responsibility solely of the waste generator. Container disposal: Containers should be drained of all residual product prior to disposal; empty/clean containers should be recycled; incinerate or landfill when recycling is not feasible.

SECTION 14 - TRANSPORT INFORMATION

Shipping description

DOT: Not regulated as hazardous for transport

IMDG: Not regulated IATA:

Not regulated

SECTION 15 - REGULATORY INFORMATION

Safety, health and environmenbtal regulations/legislation specific for the substance or mixture

SARA Title III Section 311/312 (40CFR370): Acute health hazard SARA Title III Section 313 (40CFR372): No reportable components CERCLA Statue (40CFR302): No reportable quantity components

TSCA Inventory Status: Reported/included Canadian DSL Status: Reported/included Canadian WHMIS Classification: D2B

Chemicals known to the State of California to cause cancer or reproductive toxicity:

None

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING! This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

1333-86-4 CARBON BLACK 1 - 5%

Country

Regulation

All Components Listed

EU Risk Phrases

Safety Phrase

SECTION 16 - OTHER INFORMATION

HMIS ratings:

Health 2

Flammability 1

Reactivity 1

(Personal protective equiment selection is best assigned by the user after performing a hazard assessment on the product as it is to be used in the specific work process.)

This information or recommendations contained herein are based on standard product and are proprietary and furnished solely for the use of our customers. This information is provided in good faith and believed to be true and accurate as of the date shown below; however since we have no control over the use conditions or production processes of parties using this product, Madewell Products Corp. cannot accept responsibility for loss, injury or other damages resulting from the use of the product or this or any other information provided by us. Therefore, no guarantees of any kind expressed or implied are made by Madewell Products Corp. with regard to any of their products. Users are advised to perform their own tests and hazard assessments to determine the safety, suitability and relevance of applicable law to the product as it is to be used by them.

SDS for: 806 B SPRAYABLE

Page 5 of 6

Reviewer Revision

Date Prepared: 6/30/2020

PCL XL error

Warning:

IllegalMediaSource

Warning:

IllegalMediaSource

Warning:

IllegalMediaSource

Warning:

IllegalMediaSource

Warning:

IllegalMediaSource

Warning:

IllegalMediaSource