SAFETY DATA SHEET

MADEWELL PRODUCTS CORPORATION 7561-A INDUSTRIAL COURT ALPHARETTA, GA 30004 TELEPHONE: (770) 475-8199 EMERGENCY: PERS

1-800-633-8253

SECTION 1 – IDENTITY INFORMATION

PRODUCT NAME: MAINSTAY DS-5S COMPONENT A

CHEMICAL FAMILY: Epoxy Amine (solvent free)

SUPPLIER: Madewell Products Corporation

SECTION 2 – HAZARDOUS IDENTIFICATION

Classification: Skin and Eye irritant. Dangerous for the environment.

Skin Contact: May be irritation to skin upon prolonged or repeated contact: may cause

sensitization by skin contact.

Eve contact: May cause irritation.

Inhalation: No adverse effects expected due to the physical properties of the material.

This products is classified as hazardous as defined with the OSHA Hazard Communication Standard 29CFR1910.1200.

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT	%	CAS#	LD50	ACGIH TLV	OSHA PEL
Bisphenol 'A'/Epichlorohydrin					
based epoxy	30-50	25068-38-6	11.4g/kg rat oral		
Aliphatic Glycidyl Ether	5-7	68609-96-1	No data available		
Talc	15-20	14807-96-6	No data available 2		2(mg/m3 as
					Resp Dust
Quartz	30-50	14808-60-7	No data available 0.1		0.1 (mg/m3 as
					Resp Dust
A	1.2	7(21.96.0	NI - 4-4- A11-1-1	1. 10	((2
Amorphous Silica	1-3	7631-86-9	No data Availab	ie 10	6 (mg.m3 as
					Resp. Dust)

SECTION 4 - EMERGENCY AND FIRST AID PROCEDURES

Eye Contact: Immediately flush with large amounts of water for 15 minutes. Immediately seek medical help.

Skin Contact: Wash thoroughly with soap and water or waterless hand cleaner. Remove contaminated clothing. Wash all contaminated clothing before reuse.

Inhalation: Remove victim to fresh air. Immediately seek medical help.

Ingestion:Drink water, induce vomiting by sticking finger down throat. Immediately seek medical assistance. DO NOT ATTEMPT TO GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

SECTION 5 - FIRE FIGHTING MEASURES

Flammability Classification: Not flammable

Flash Point: >200 C

Upper and lower flammable limits not established for the product

Extinguishing Media: Use water fog, foam, dry chemical or carbon dioxide.

Unusual Fire and Explosion Hazards: Keep containers tightly closed. isolate from heat, electrical equipment, sparks and open flame. Closed containers may explode when exposed to extreme heat. application to hot surfaces require special precautions. during emergency conditions overexposure to decomposition products may cause a health hazard. symptoms may not be immediately apparent. Obtain medical attention.

Special Fire Fighting Procedures: When heated vapours/decomposition products may be released forming flammable/explosive mixtures in air. Closed containers may explode when exposed to extreme heat.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions: Isolate area; keep unnecessary and unprotected personnel from entering the involved area; avoid contact with skin, eyes, and clothing.

Environmental Precautions: Prevent contamination of soil and water. Prevent from spreading or entering into drains, ditches, waterways by using sand, earth or appropriate barriers.

Methods for Cleaning Up: Soak up with inert absorbent material, collect into closeable labeled containers and dispose of in accordance with applicable local and federal environmental control regulations.

SECTION 7 - HANDLING AND STORAGE

Handling:Observe good personal hygiene practices and recommended procedures. Avoid prolonged or repeated breathing of vapors, mists or fumes. Avoid prolonged or repeated contact with skin and eyes.

Storage: Store in a cool, dry place with adequate ventilation. Keep away from open flames.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

Eye Protection: Industrial safety glasses as necessary to comply with 29 CFR 1910.133 as dictated by work area conditions.

Skin Protection: Impervious coveralls, rubber safety boots, cap and rubber gloves. Apply barrier cream to exposed areas of face.

Respiratory Protection: Full face piece respiratory units required when spraying this material, comination filter/organic vapor catridges or canisters may be used. TVL (PEL) use NIOSH/OSHA sel contained breathing apparatus.

Engineering Controls: Provide sufficient ventilation through local exhaust.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE VISCOUS LIQUID SPECIFIC GRAVITY 1.594 AT 20 C

BOILING POINT 200 C

VAPOR PRESSURE <0.001mmHg@ 32 C

ODOUR SLIGHT ETHEREAL ODOUR

DECOMPOSITION TEMP. >200 C

% VOLATILE LESS THAN 0.5% AT 70F

SOLUBILITY IN WATER INSOLUBLE STABILITY STABLE

HAZ. POLYMERIZATION WILL NOT OCCUR

SECTION 10 - STABILITY AND REACTIVITY

Stability: Stable at ambient temperatures Conditions to Avoid: Elevated temperatures Materials to Avoid: Strong oxidizing agents

Hazardous Decomposition Products: UBy Fire: carbon monoxide, aldehydes

Hazardous Polymerization Will not occur.

SECTION 11 - TOXICOLOGICAL INFORMATION

Acute Oral Toxicity: LD50(rat) 11.4g/kg

Acute Dermal Toxicity: LD50(rabbit): 20,000 mg/kg

SECTION 12 - ECOLOGICAL INFORMATION

Bioegradability: Not readily biodegradable; moderate potential to bioconcentrate. **Ecotoxicity Effects:** Data for this type product indicate that the material is moderately toxic to aquatic organisms on an acute basis where the LC50 for the most sensitive species is 1-10 mg/L; however, the toxicity to aquatic species occurs at concentrations greater than the water solubility of the material.

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal: Do not dump to ground, sewers or watercourses. All methods of disposal must be in compliance with all applicable federal, state and local laws/regulations: regulations may vary in different locations. Waste characterization and compliance with applicable laws are the responsibility solely of the generator.

Container Disposal: Containers should be drained of all residual products prior to disposal.

SECTION 14 - TRANSPORT INFORMATION

DOT: Not regulated. **IMDG:** Not regulated. **IATA:** Not regulated.

Safety phrases:

SECTION 15 - REGULATORY INFORMATION

SARA Title III Section 311/312 (40CFR370): Acute health hazard. SARA Title III Section 313 (40CFR372): No Reportable Components. CERCLA Status (40CFR302): No reportable Quantity components.

TSCA Inventory Status: Reported/included Canadian DSL Status: Reported/included

Canadian WHMIS Classification: D2B (eye or skin irritant; skin sensitizer)

OSHA/NTP/IARC Carcinogen Status: Not listed.

Chemicals Known to the State of California to Cause Cancer or Reproductive

Toxicity: None known to be in the products at levels requiring a warning.

Risk phrases: R36/38 Irritating to eyes and skin

R43 May cause sensitization by skin contact

R51/53 Toxic to aquatic organisms, may cause long-term adverse

effects to the aquatic environment. S2 Keep out of the reach of children

S28 After contact with skin, wash immediately with plenty of

water

S37/39 Wear Suitable gloves and eye/face protection

S61 Avoid release to the environment: refer to special instructions/

sds

Hazard Symbols: Xi Irritant, N Dangerous for the Environment

SECTION 16 - OTHER INFORMATION

HMIS Ratings: Health: 2

Flammability 1 Reactivity: 0

(Personal protective equipment selection is best assigned by the user after performing a hazard assessment on the product as it is to be used in the specific work process.)

THE INFORMATION OR RECOMMENDATIONS O CONTAINED HEREIN ARE BASED ON STANDARD PRODUCT AND ARE PROPRIETARY AND FURNISHED SOLELY FOR THE USE OF OUR CUSTOMERS. THIS INFORMATION IS PROVIDED IN GOOD FAITH AND BELIEVED TO BE TRU AND ACCURATE AS THE DATE SHOWN ABOVE. HOWEVER, SINCE WE HAVE NO CONTROL OVR THE USE CONDITIONS OR PRODUCTION PROCESSES OF PARTIES USING THIS PRODUCT. MADEWELL PRODUCTS CORP CANNOT ACCEPT RESPONSIBILITY FOR LOSS, INJURY OR OTHER DAMAGES RESULTING FROM THE USE OF THE PRODUCT OR THIS OR ANDY OTHER INFOORMATION PROVIDED BY US. THEREFORE, NO GUARANTEES OF ANY, EXPRESSED OR IMPLIED, ARE MADE BY MADEWELL PRODUCTS CORP WITH REGARD TO ANY OF THEIR PRODUCTS. USERS ARE ADVISED TO PERFORM THEIR OWN TESTS AND HAZARD ASSESSMENTS TO DETERMINE THE SAFETY, SUITABILITY AND RELEVANCE OF APPLICABLE LAW TO THE PRODUCT AS IT IS TO BE USED BY THEM.

\MAD\SDS DS5S A 2013